

THE ID PACK PRODUCT RANGE



THE RIGHT
ID PACK
FOR YOUR
APPLICATION



In Development – Expected in 2022

	ID PACK 24 x 32	ID PACK 59 x 48	ID PACK 63 x 48
Outside dimensions (L x W x H)	32.48" x 24.02" x 27.52" 825 x 610 x 699 mm	59.06" x 48.23" x 51.30" 1500 x 1225 x 1096 mm	63.98" x 48.23" x 51.30" 1625 x 1225 x 896 mm
Inside dimensions (L x W x H)	29.60" x 21.54" x 20.39" 752 x 547 x 518 mm	56.22" x 45.08" x 35.91" 1428 x 1145 x 912 mm	60.63" x 45.08" x 28.03" 1540 x 1145 x 712 mm
Volume	7.52 ft ³ / 213 L	52.65 ft ³ / 1491 L	44.32 ft ³ / 1255 L
Netto payload weight acc. To ASTM 4169-16	330 lb / 150 kg	1100 lb / 500 kg	1100 lb / 500 kg
Permissible top load acc. To ASTM 4169-16	1450 lb / 660 kg	4850 lb / 2200 kg	4850 lb / 2200 kg
Tare weight	36 lb / 16.5 kg	108 lb / 49 kg	115 lb / 52 kg
Volume reduction	93 %	95 %	95 %



	ID PACK 24 x 32	ID PACK 59 x 48	ID PACK 63 x 48
A*	54.9" / 1395 mm	102.0" / 2591 mm	102.0" / 2591 mm
B	27.52" / 699 mm	51.30" / 1303 mm	51.30" / 1303 mm
C	3.70" / 94 mm	3.74" / 95 mm	3.74" / 95 mm
D*	18.43" / 468 mm	18.58" / 472 mm	18.66" / 474 mm
E	9.52" / 242 mm	9.25" / 235 mm	9.25" / 235 mm

* Subtract 0.55" (14 mm) per stack interface to account for stack nesting.

All values given are approximate.

**THE RIGHT
ID PACK
FOR YOUR
APPLICATION**



	ID PACK 32 x 48	ID PACK 40 x 48	ID PACK 45 x 48
Outside dimensions (L x W x H)	32.48" x 48.23" x 35.28" 825 x 1225 x 896 mm	40.35" x 48.23" x 43.15" 1025 x 1225 x 1096 mm	45.08" x 48.23" x 46.81" 1145 x 1225 x 1189 mm
Inside dimensions (L x W x H)	29.33" x 45.08" x 28.03" 745 x 1145 x 712 mm	37.20" x 45.08" x 35.91" 945 x 1145 x 912 mm	42.40" x 45.16" x 39.57" 1077 x 1147 x 1005 mm
Volume	21.44 ft ³ / 607 L	34.86 ft ³ / 987 L	43.30 ft ³ / 1226 L
Payload weight*	1100 lb / 500 kg	1100 lb / 500 kg	1100 lb / 500 kg
Permissible top load*	4850 lb / 2200 kg	4850 lb / 2200 kg	4850 lb / 2200 kg
Tare weight	51 lb / 23 kg	64 lb / 29 kg	73 lb / 33 kg
Volume reduction	74 %	79 %	80 %



	ID PACK 32 x 48	ID PACK 40 x 48	ID PACK 45 x 48
A**	70.04" / 1779 mm	85.75" / 2178 mm	87.28" / 2217 mm
B	35.28" / 896 mm	43.15" / 1096 mm	46.81" / 1189 mm
C	3.74" / 95 mm	3.74" / 95 mm	3.74" / 95 mm
D**	17.95" / 456 mm	17.95" / 456 mm	17.95" / 456 mm
E	9.25" / 235 mm	9.25" / 235 mm	9.25" / 235 mm

* Tested by the VDZ competence and testing center for packaging and transport, Giselherstr. 34, 44319 Dortmund, Germany (certificate number: 8021). Permissible top load may vary due to the level of assurance (level I, level II, level III).

** Subtract 0.55" (14 mm) per stack interface to account for stack nesting.



ID Plastics, LP
2175 Pumphrey Ave
Auburn, Alabama,
36832, USA

Phone: +1 334-209-0797
sales@id-plastics.com
www.id-plastics.com